



Logo Placements

1162 ProtecWork, Waterproof Insulated Hood Jacket High-Vis Class 3

Recommended logo placements

Heat seal

- 1 Left breast, 1 cm above pocket
- 2 Left sleeve, 5 cm below shoulder seam
- 3 Right breast, 1 cm above yoke seam
- 4 Right sleeve, 5 cm below shoulder seam
- 6 Back, 2 cm below yoke seam (Jacket has detachable hood)
- 23 Right breast, top of logo in line with top of zipper
- 24 In top of left breast pocket

Maximum Size		
Place ment	Embroid ery	Heat seal
1	-	70x70
3	-	70x70
2	-	100x100
4	-	100x100
6	200x270	200x280
23	-	120x100
24	-	80x80
62	270x200	280x200



Maximum size of logo cm² to keep classification EN 20471

Size All cm² 850 cm 28x28




How to keep classification ISO EN 11612

To maintain the Class 3 certification, see maximum logo size in table to the right.
If you choose a logo bigger than our recommendation, we do not guarantee that the garment, meets the EN 20471 Norm.

When you place the logo on dark fabric, it has no impact on the EN 20471 Norm

When ordering embroidery you need to have both article no. for embroidery and for waterproof film (EMB99990000019 (small) or EMB99990000029 (big), to avoid water coming through



Add

B after the placement and it will be below the (1B)

Y and it will be turned from bottom to top

Z after the placement and it will be turned from top to bottom

Labels, badges, retro-reflective materials, transfers, etc., which are applied to the outermost surface of the garment, with an area > 10 cm² shall be tested in ISO 15025, Procedure A.

