



# Logo Placements

## 1361 Waterproof Jacket, HV Class 3

### Recommended logo placements

#### Heat seal

- 1 Left breast, 1 cm above seam
- 3 Right breast, 1 cm above seam
- 4 Right sleeve, 5 cm below shoulder seam
- 6 Back, 2 cm below yoke seam,
- 23 Right breast, top of logo in line with top of zipper
- 24 Center in middle of left breast pocket
- 62 Back, 13 cm below yoke seam

| Maximum Size |             |           |
|--------------|-------------|-----------|
| Place ment   | Embroid ery | Heat seal |
| 1            | 60x60       | 70x70     |
| 3            | 60x60       | 70x70     |
| 2            | 100x30      | 100x80    |
| 4            | 100x30      | 100x80    |
| 6            | 200x270     | 200x280   |
| 23           | 100x80      | 120x100   |
| 24           | -           | 70x100    |
| 62           | 270x200     | 270x200   |



Maximum size of logo cm<sup>2</sup> to keep classification EN 20471

| Size  | cm <sup>2</sup> | cm    |
|-------|-----------------|-------|
| XS    | 80              | 9x9   |
| S     | 720             | 26x26 |
| M-XXL | 1350            | 36x36 |

To maintain 3 certification, see maximum logo size in table to the right. If you choose a logo bigger than our recommendation, we do not guarantee that the garment meets the EN 20471 Norm.

Add



B after the placement and it will be below the (1B)

Y and it will be turned from bottom to top

Z after the placement and it will be turned from top to bottom



How to keep classification ISO EN 11612

Labels, badges, retro-reflective materials, transfers, etc., which are applied to the outermost surface of the garment, with an area > 10 cm<sup>2</sup> shall be tested in ISO 15025, Procedure A.

