



Logo Placements

6262 PW Trousers HP

Recommended logo placements

Heat seal & Embroidery

- 11 Rear side of left leg (calf), centered between the seams, start 5 above lowest point of leg.
- 16 Rear side of right leg (calf), centered between the seams, start 5 above lowest point of leg.
- 28 Rear side of right leg, 1 cm from side seam, start 5 above lowest point of leg.
- 34 Rear side of left leg, 1 cm from side seam, start 5 above lowest point of leg.
- 100 Right leg, 2 cm above reflective, maximum size 120x100
- 101 Left leg, centered 2 cm above pocket seam, maximum size 100x100mm

Heat seal

- 18 Centered, 2 cm below pocket seam, maximum size 120x80 mm
- 19 Right leg pocket, maximum size 100x40 mm
- 20 Left leg pocket, maximum size 100x40 mm
- 29 Right thigh-pocket flap, maximum size 30x120 mm
- 30 Left thigh-pocket flap, maximum size 30x100 mm
- 42 Centred at left front holster-pocket, maximum size 120x50 mm

Placement 11, 16, 28 and 34 maximum size,
for embroidery 250x80 mm and for heat seal 300x200 mm

- Add
- 1Y B after the placement and it will be below the (1B)
 - 1B Y and it will be turned from bottom to top
 - 1Z Z after the placement and it will be turned from top to bottom



How to keep
classification
ISO EN 11612

Labels, badges, retro-reflec-
tive materials, transfers, etc.,
which are applied to the
outermost surface of the
garment, with an area > 10
cm² shall be tested in ISO
15025, Procedure A.



Right side of trouser



Left side of trouser

