



Logo Placements

8261 Rain Jacket, CI 3

Recommended logo placements

Heat seal

- 1 Left breast, maximum size 120x120 mm
- 2 Left sleeve, 20 cm below neck seam, maximum size 120x120 mm
- 3 Right breast, maximum size 120x120 mm
- 4 Right sleeve, 20 cm below neck seam, maximum size 120x120 mm
- 5 Back, 1 cm above yoke seam, maximum size 280x120 mm
- 6 Back, 2 cm below yoke seam, maximum size 280x120 mm
- 62 Back, center between reflective bands, maximum size 280x140 mm
- 63 Back, 2 cm above end seam, maximum size 280x160 mm

To maintain the Class 3 certification, see maximum logo size in table to the right.

If you choose a logo bigger than our recommendation, we do not guarantee that the garment meets the EN 20471 Norm.

- Add
- 1Y B after the placement and it will be below the (1B)
 - 1B Y and it will be turned from bottom to top
 - Z Z and it will be turned from top to bottom



Maximum size of logo cm² to keep classification EN 20471

Size	cm ²	cm
All	1800	42x42



How to keep classification ISO EN 11612

Labels, badges, retro-reflective materials, transfers, etc., which are applied to the outermost surface of the garment, with an area > 10 cm² shall be tested in ISO 15025, Procedure A.

